MOTIP DUPLI Revision: 11.06.2015

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

· 1.1 Product identifier

Version number 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking · Trade name: MOTIP TUNING LINE BACKLIGHT Black / Red

· Article number: 00260 / 00261

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against --· Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: MOTIP DUPLI GmbH Kurt Vogelsang Strasse 6 D-74855 Haßmersheim Tel.: +49/6266/75-0 msds@dupli-color.de · Further information obtainable from: Department Product Safety · 1.4 Emergency telephone number:
- Tel.:+49 6266-75-310
- Fax +49 6266-75-362
- (Mo Th 08:00 am 04:00 pm, Fr 08:00 am 00:30 pm)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

GHS07

Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

acetone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB

Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

Version number 4

Revision: 11.06.2015

(Contd. of page 1)

Trade name: MOTIP TUNING LINE BACKLIGHT Black / Red

· Precautionary statements

- *P101* If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

• Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	🚸 Flam. Liq. 2, H225; 1 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane 🚸 Flam. Gas 1, H220; Press. Gas C, H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane 🚸 Flam. Gas 1, H220; Press. Gas C, H280	12.5-<20%
CAS: 64742-48-9 EINECS: 265-150-3 Index number: 649-327-00-6 Reg.nr.: 01-2119486659-16	Naphtha (petroleum), hydrotreated heavy	5-<10%
CAS: 64742-82-1 EINECS: 265-185-4 Index number: 649-330-00-2 Reg.nr.: 01-2119490979-12	Naphtha (petroleum), hydrodesulfurized heavy Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane 🚸 Flam. Gas 1, H220; Press. Gas C, H280	2.5-<5.0%
CAS: 108-67-8 EINECS: 203-604-4 Index number: 601-025-00-5	mesitylene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; STOT SE 3, H335	<i>≤</i> 0.5%
CAS: 95-63-6 EINECS: 202-436-9 Index number: 601-043-00-3	1,2,4-trimethylbenzene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≤0.5%

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

Version number 4

Revision: 11.06.2015

(Contd. of page 2)

Trade name: MOTIP TUNING LINE BACKLIGHT Black / Red

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- \cdot Suitable extinguishing agents:
- CO2, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim. Vaten met water afkoelen.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources. Ensure adequate ventilation Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. Do not allow product to reach sewage system or any water course.
- \cdot 6.3 Methods and material for containment and cleaning up:
- Do not flush with water or aqueous cleansing agents Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

 \cdot 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

[–] Gl

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

Version number 4

Revision: 11.06.2015

Trade name: MOTIP TUNING LINE BACKLIGHT Black / Red

(Contd. of page 3)

Open and handle receptacle with care. • Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- *Requirements to be met by storerooms and receptacles:* Store in a cool location. Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Storage class: 2B

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:

General protective and hygienic measures: Do not eat, drink, smoke or sniff while working. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

- **Respiratory protection:** Not necessary if room is well-ventilated. Otherwise, filter class A / P2 or self contained.
- · Protection of hands:



Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Butyl rubber, BR

(Contd. on page 5)

GB

Page 5/9

L

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

Version number 4

Revision: 11.06.2015

• Penetration time of glove material Butyl rubber gloves with a thickness	(Contd. of pa of 0.4 mm are resistant to:	ge 4
Acetone: 480 min Butyl acetate: 60 min		
Ethyl acetate: 170 min Xylene: 42 min		
• Eye protection: Safety glasses		
• Body protection: Light weight prote	ctive clothing	
SECTION 9: Physical and ch	emical properties	
• 9.1 Information on basic physical a • General Information	and chemical properties	
· Appearance: Form:	Aerosol	
Colour:	According to product specification	
· Odour:	Characteristic	
• Odour threshold:	Not determined. Not determined.	
· pH-value: · Change in condition	Noi determined.	
Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Not applicable, as aerosol.	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C	
• Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
• Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.	
· Explosion limits:	15 1/21 0/	
Lower: Upper:	1.5 Vol % 13.0 Vol %	
· Vapour pressure at 20 °C:	8300 hPa	
· Density at 20 °C:	0.74 g/cm ³	
· Relative density	Not determined.	
 Vapour density Evaporation rate 	Not determined. Not applicable.	
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content: VOC-(EU)		
	670.1 g/l	
· VOC-EU%	90.09 %	
· Solids content:	16.6 %	

Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

Version number 4

Revision: 11.06.2015

Trade name: MOTIP TUNING LINE BACKLIGHT Black / Red

(Contd. of page 5)

• 9.2 Other information

 $No\ further\ relevant\ information\ available.$

SECTION 10: Stability and reactivity

· 10.1 Reactivity

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

67-64-1 ac	etone			
Oral	LD50	5800 mg/kg (rat)		
Dermal	LD50	20000 mg/kg (rabbit)		
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy			
Oral	LD50	>5000 mg/kg (rat)		
Dermal	LD50	>3000 mg/kg (rab)		
64742-82	64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy			
Oral	LD50	>5000 mg/kg (rat) (OECD 403)		
Dermal	LD50	>2000 mg/kg (rat)		
Inhalative	LC50/4 h	>13.1 mg/l (rat) (OECD 403)		
Driman in	witant offo	· · · · · · · · · · · · · · · · · · ·		

· Primary irritant effect:

• Skin corrosion/irritation No irritant effect.

- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

Vapours have narcotic effect.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic tox	icity:	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	
EC50/48h	43.98 mg/l (bel) (berechnet)	
	10-20 mg/l (daphnia magna / Wasserfloh) (OECD 202)	
NOEC	0.22 mg/l (Pseudokirchneriella subcapitata) (OECD 201 (72h))	
· 12.3 Bioacc	ence and degradability No further relevant information available. umulative potential No further relevant information available. ty in soil No further relevant information available.	
		(Contd. on page 7) GB

Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

Version number 4

Revision: 11.06.2015

Trade name: MOTIP TUNING LINE BACKLIGHT Black / Red

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

-	waste catalogue
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging
	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

· Uncleaned packaging:

×

• Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
·ADR	UN1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	
· 14.3 Transport hazard class(es)		
·ADR		
· Class	2 5F Gases.	
· Label	2.1	
· IMDG, IATA		
· Class	2.1	
· Label	2.1	
· 14.4 Packing group		

(Contd. of page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

Version number 4

Revision: 11.06.2015

Trade name: MOTIP TUNING LINE BACKLIGHT Black / Red

	(Con	td. of page 7)
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Gases.	
· Danger code (Kemler):	-	
· EMS Number:	F- D , S - U	
· 14.7 Transport in bulk according to Anne	x II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	1L	
Excepted quantities $(\widetilde{E}Q)$	Code: E0	
• • • ~	Not permitted as Excepted Quantity	
· Transport category	2	
Tunnel restriction code	D	
·IMDG		
· Limited quantities (LQ)	1L	
· Excepted quantities $(\widetilde{E}Q)$	Code: E0	
	Not permitted as Excepted Quantity	
· UN ''Model Regulation'':	UN1950, AEROSOLS, 2.1	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. · Contact: Anwendungstechnik · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

(Contd. on page 9)

GB

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.06.2015

Version number 4

Revision: 11.06.2015

Trade name: MOTIP TUNING LINE BACKLIGHT Black / Red

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Gas 1: Flammable gases, Hazard Category 1 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas C: Gases under pressure: Compressed gas Flam. Liq. 2: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity. Hazard Category 4	(Contd. of page 8)
Acute Tox. 4: Acute toxicity, Hazard Category 4	
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3	
Asp. Tox. 1: Aspiration hazard, Hazard Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2	
	GB