

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

1 Identification of the substance/mixture and of the company/undertaking · Product identifier · Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH · Article number: 04033 · Relevant identified uses of the substance or mixture and uses advised against · Application of the substance / the preparation Paint · Details of the supplier of the safety data sheet · Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL-8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com • Further information obtainable from: QHSE Department • Emergency telephone number: Tel: +31 (0)561 694400 (08.00 / 17.00) 2 Hazards identification · Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Aerosol 1 H222 Extremely flammable aerosol. GHS05 corrosion Eve Dam. 1 H318 Causes serious eye damage. GHS07 STOT SE 3 H336 May cause drowsiness or dizziness. Classification according to Directive 67/548/EEC or Directive 1999/45/EC 💢 Xi; Irritant R36: Irritating to eyes. F+; Extremely flammable R12: Extremely flammable. *R66-67*: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. · Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurized container. Has a narcotizing effect.

Page 2/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

### Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

• Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

*The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.* 

### · Code letter and hazard designation of product:



*Xi* Irritant *F*+ Extremely flammable

### · Risk phrases:

12 Extremely flammable.

36 Irritating to eyes.

- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

### · Safety phrases:

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe aerosol.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.
- Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- Other hazards
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous compon	ents:	
CAS: 67-64-1	acetone	25-50%
EINECS: 200-662-2	🗙 Xi R36	
	F R11	
	<b>R</b> 66-67	
	🚸 Flam. Liq. 2, H225	
	<b>Eye Irrit.</b> 2, H319; STOT SE 3, H336	
CAS: 74-98-6	propane	12.5-20%
EINECS: 200-827-9	F + R12	
	<b>Flam.</b> Gas 1, H220	
	Press. Gas, H280	
L	(Co	ntd. on page 3)

(Contd. of page 1)

Page 3/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

### Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

CAS: 106-97-8	butane	(Contd. of pa 10-12.
EINECS: 203-448-7		10-12.
EINECS: 205 770 7	Solution Flam. Gas 1, H220	
	Press. Gas, H280	
CAS: 75-28-5	isobutane	5-10
EINECS: 200-857-2	<u>v</u>	
	Flam. Gas 1, H220 Press. Gas, H280	
CAS: 78-93-3	butanone	5-10
EINECS: 201-159-0		
	<i>F R</i> 11 <i>R</i> 66-67	
	<ul> <li>Flam. Liq. 2, H225</li> <li>Eye Irrit. 2, H319; STOT SE 3, H336</li> </ul>	
CAS: 123-86-4	n-butyl acetate	5-10
EINECS: 204-658-1		
	<ul> <li>Flam. Liq. 3, H226</li> <li>STOT SE 3, H336</li> </ul>	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5-5
EINECS: 203-603-9		
	🚸 Flam. Liq. 3, H226	
CAS: 71-36-3	butan-1-ol	2.5-5
EINECS: 200-751-6		
	Xi R37/38-41 R10-67	
	🚸 Flam. Liq. 3, H226	
	Eye Dam. 1, H318	
	Acute Tox. 4, H302; STOT SE 3, H335+H336	
G ( G 1220 20 7	Skin Irrit. 2, H315	
CAS: 1330-20-7 EINECS: 215-535-7	xylene	1-2.5
EINECS: 213-333-/	Xn R20/21 Xi R38	
	R10	
	Flam. Liq. 3, H226	
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	

### 4 First aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

# **5** Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

<sup>-</sup> GB

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

(Contd. of page 3)

### Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources.
   Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Ensure adequate ventilation.
- Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling
- No special measures required. Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
   Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles: Store in a cool location.*
- Observe official regulations on storing packagings with pressurized containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Protect from heat and direct sunlight.

• Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm

Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

(Contd. on page 5)

GB

Page 5/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

## Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

106_01	7-8 butane		(Contd. of pag
	Short-term value: 1810 mg	$a/m^3 750 nnm$	
	Long-term value: 1450 mg		
	Carc (if more than 0.1% o		
	3 butanone		
	Short-term value: 899 mg/	/m <sup>3</sup> 200 ppm	
	Long-term value: 600 mg/		
	Sk	<i>m</i> , 200 <i>ppm</i>	
	6-4 n-butyl acetate		
	Short-term value: 966 mg/	/m <sup>3</sup> . 200 ppm	
	Long-term value: 724 mg/		
	5-6 2-methoxy-1-methylet		
	Short-term value: 548 mg/	-	
	Long-term value: 274 mg/		
	Sk		
71-36-	-3 butan-1-ol		
	Short-term value: 154 mg/	$/m^{3}$ , 50 ppm	
	Skori ierm value. 194 mg/ Sk	···· , - ~ pp···	
	20-7 xylene		
	Short-term value: 441 mg/	/m <sup>3</sup> , 100 ppm	
	Long-term value: 220 mg/		
	Sk; BMGV		
Avoid Avoid Respir Protec Materi Penetr	t inhale gases / fumes / aer contact with the eyes. contact with the eyes and catory protection: Not requir- tion of hands: Not requir- ial of gloves Not required. cation time of glove mater cotection: Tightly sealed goggle	skin. uired. red. r <b>ial</b> Not required.	
Inforn	ical and chemical pro nation on basic physical a al Information rance:	*	
Appea Forn Colo	n:	Aerosol According to product specification	
Appea Form Colo Odour	n: our: ::		
Appea Form Colo Odour	n: pur:	According to product specification	

Page 6/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

### Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

pH-value:	(Contd. of pag Not determined.
	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	$< 0^{\circ}C \ (< 32^{\circ}F)$
	Not applicable, as aerosol.
Ignition temperature:	365°C (689°F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/
	vapour mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20°C (68°F):	3500 hPa (2625 mm Hg)
Density at 20°C (68°F):	0.715 g/cm³ (5.967 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Segregation coefficient (n-octanol/wa	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	93.1 %
EU-VOC:	686.8 g/l
EU-VOC in %:	96.06%
Solids content:	6.9 %
Other information	No further relevant information available.

# 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

Page 7/10

\*

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

### Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

(Contd. of page 6)

Acute to	•	levant for classification:
	acetone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
	LC50 / 4 h	39 mg/m3 (rat)
106-97-	8 butane	
	LC50 / 4 h	658 mg/m3 (rat)
78-93-3	butanone	
Oral	LD50	2737 mg/kg (rat)
Dermal	LD50	6480 mg/kg (rabbit)
	LC50 / 4 h	34 mg/m3 (rat)
123-86-	4 n-butyl ac	etate
Oral	LD50	10770 mg/kg (rat)
Dermal	LD50	>17600 mg/kg (rabbit)
	LC50 / 4 h	>21.0 mg/m3 (rat)
108-65-	6 2-methox	y-1-methylethyl acetate
Oral	LD50	8532 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
	LC50 / 4 h	35.7 mg/m3 (rat)
71-36-3	butan-1-ol	
Oral	LD50	4400 mg/kg (rat)
Dermal	LD50	4200 mg/kg (rabbit)
	LC50 / 4 h	25 mg/m3 (rat)
1330-20	)-7 xylene	
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
	LC50 / 4 h	22.1 mg/m3 (rat)
	v irritant eff	
	<b>kin:</b> No irri <b>ye:</b> Irritatin	
		g ejjeci. ensitizing effects known.

# 12 Ecological information

• Toxicity		
• Acquatic toxicity:		
67-64-1 acetone		
EC50 / 48 h	39 mg/l (daphnia magna)	
LC50 / 48 h	2262 mg/l (daphnia magna)	
LC50 / 96 h (static)	5540 mg/l (fish)	

(Contd. on page 8)

GB

Page 8/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011


### Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

		(Contd. of page 7)
123-86-4 n-butyl (		
EC50 / 96 h	320 mg/l (algae)	
LC50 / 24 h	205 mg/l (daphnia magna)	
108-65-6 2-metho.	xy-1-methylethyl acetate	
EC50	408 mg/l (daphnia magna)	
71-36-3 butan-1-0	l l	
EC50 / 48 h	1983 mg/l (daphnia magna)	
EC50 / 72 h	8500 mg/l (algae)	
1330-20-7 xylene		
EC50 / 48 h	7.4 mg/l (daphnia magna)	
LC50 / 96 h	13.5 mg/l (fish)	
Additional ecology General notes: Water hazard class Do not allow prod Danger to drinking Results of PBT an PBT: Not applical vPvB: Not applical	s 2 (German Regulation) (Self-assessment): hazardous for water uct to reach ground water, water course or sewage system. g water if even small quantities leak into the ground. d <b>vPvB assessment</b> ble.	
· European waste c	<b>nethods</b> red together with household garbage. Do not allow product to reach sewag <b>atalogue</b> paint and varnish containing organic solvents or other dangerous substanc	
· Uncleaned packag		

• *Recommendation:* Disposal must be made according to official regulations.

# 14 Transport information

· Land transport ADR/RID (cross-border)



(Contd. on page 9)

GB

Page 9/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

# Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

Tunnel restriction code	D	
Maritime transport IMD	G:	
IMDG Class:	2.1	
· UN Number:	1950	
· Label	2.1	
· Packaging group: · EMS Number:	- F-D,S-U	
• <i>Marine pollutant:</i>	No	
Proper shipping name:	AEROSOLS	
· Air transport ICAO-TI ai	nd IATA-DGR:	
V		
· ICAO/IATA Class:	2.1	
· UN/ID Number:	1950	
· Label	2.1	
· Packaging group:	-	
• Proper shipping name:	AEROSOLS, flammable	
	: UN1950, AEROSOLS, 2.1	

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

# **15 Regulatory information**

### · Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to EU guidelines:

*The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.* 

Code letter and hazard designation of product:



*Xi* Irritant *F*+ Extremely flammable

### · Risk phrases:

- 12 Extremely flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

### · Safety phrases:

- 2 Keep out of the reach of children.
- *Keep away from sources of ignition No smoking.*
- 23 Do not breathe aerosol.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2011

Version number 30

Revision: 23.03.2011

### Trade name: MOTIP HEAT RESISTANT CLEAR VARNISH

(Contd. of page 9)

• Special labelling of certain preparations:

*Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.* 

Do not spray on a naked flame or any incandescent material.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R22 Harmful if swallowed.
- *R36 Irritating to eyes.*
- R37/38 Irritating to respiratory system and skin.
- R38 Irritating to skin.
- *R41 Risk of serious damage to eyes.*
- *R66 Repeated exposure may cause skin dryness or cracking.*
- *R67* Vapours may cause drowsiness and dizziness.

### · Department issuing MSDS: QHSE Department

- · Contact:
- Mrs. D. Kleistra

### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent \* Data compared to the previous version altered.